

Asymptotic Bounds for Quantitative Verification of Perturbed Probabilistic Systems

Guoxin Su and David S. Rosenblum

National University of Singapore

Abstract. The majority of existing probabilistic model checking case studies are based on well understood theoretical models and distributions. However, real-life probabilistic systems usually involve distribution parameters whose values are obtained by empirical measurements and thus are subject to small perturbations. In this paper, we consider perturbation analysis of reachability in the parametric models of these systems (i.e., parametric Markov chains) equipped with the norm of absolute distance. Our main contribution is a method to compute the *asymptotic bounds* in the form of *condition numbers* for constrained reachability probabilities against perturbations of the distribution parameters of the system. The adequacy of the method is demonstrated through experiments.

1 Introduction

Probabilistic model checking is a verification technique that has matured over the past decade, and one of the most widely known and used probabilistic model checking tools is PRISM [1]. The majority of the reported case studies of probabilistic model checking, including those performed in PRISM, involve systems whose stochastic nature arises from well understood theoretical probabilistic distributions, such as the use of a fair coin toss to introduce randomization into an algorithm, or the uniform distribution of randomly chosen IP addresses in the Zeroconf protocol. More complex, realistic systems, on the other hand, involve behaviors or other system characteristics generated by empirical distributions that must be encoded via empirically observed parameters. In many cases, these distribution parameters are based on finite numbers of samples and are statistical estimations that are subject to further adjustments. Also, the stochastic nature of the model (e.g., the failure rate of some hardware component) may be varying over time (e.g., the age of the component). The conventional techniques and tools of probabilistic model checking, including PRISM, do not provide sufficient account for systems with distribution parameters. Consider, for instance, the setting of automata-based model checking: Given a (probabilistic) model $\mathcal{M}$ and an LTL formula φ , the model checker returns a satisfaction probability p of φ in $\mathcal{M}$. However, $\mathcal{M}$ is just an *idealized* model of the probabilistic system under consideration, and because the real distribution(s) of its parameter(s) may be slightly different from those specified in $\mathcal{M}$, p is merely a *referential* result whilst the *actual* result may deviate from p to a small but non-trivial extent. We elaborate this pitfall in the following two concrete examples.




Fig. 1. Zeroconf protocol with noisy channels

Motivating examples. We first present an IPv4 Zeroconf protocol model for a network with noisy communication channels. Figure 1 present the protocol model that uses a maximum of four ‘ok’ message probes. Let a be the probability that the new host chooses an IP address that has been used already, and x be the probability that the probe or its reply is lost due to channel noise or some other reason (if any). If an IP address is randomly chosen, then a is equal to m/n , where $n = 60,534$ is the size of IP address space as specified in Zeroconf and m is number of the connected hosts. By contrast, x relies on an *ad hoc* statistical estimation of the lose rate of messages tested in experiments. In reality, it is less meaningful to specify a single, constant value of x , as the measurement could be affected by factors such as net load, environment noise, temperature, measurement time, ect. Instead, x may be given as the expression $x_0 \pm x_\Delta$, where x_0 is the mean value of the measured results and x_Δ specifies the maximal perturbation. It is therefore reasonable to express the probability that an IP collision happens as the form of $y = y_0 \pm y_\Delta$, where y_0 is a referential value for the result and y_Δ specifies the range of perturbation of y . However, although the standard model checking techniques allow one to obtain y_0 by inputting x_0 , they provide little account for the relationship between y_Δ and x_Δ .

Another example is an variant of the classic hopping frog example. We suppose a frog hopping between four rocks, and the (i, j) -entry in the following *parametric transition matrix* (a matrix whose entries are either numbers or variables)

$$\begin{pmatrix} z_1 & z_2 & z_3 & z_4 \\ \frac{3}{8} & \frac{1}{8} & \frac{1}{4} & \frac{1}{4} \\ 0 & \frac{1}{2} & \frac{1}{2} & 0 \\ \frac{1}{3} & 0 & \frac{1}{3} & \frac{1}{3} \end{pmatrix}$$

present the concrete or abstract probability of frog’s movement from the i th rock to the j th rock. In this matrix, the tuple of variables (z_1, z_2, z_3, z_4) forms a distribution parameter (i.e., satisfying the constraint that $z_i \geq 0$ for each $1 \leq i \leq 4$ and $z_1 + z_2 + z_3 + z_4 = 1$) and is restricted by the following condition:

$$\left| z_1 - \frac{3}{8} \right| + \left| z_2 - \frac{1}{8} \right| + \left| z_3 - \frac{1}{4} \right| + \left| z_4 - \frac{1}{4} \right| \leq \Delta, \quad (1)$$

Table 1. Reachability checking in MCs and PMCs

Model	Input	Output
$\mathcal{M}$	$S_? \mathcal{U} S_!$	p (idealized reachability probability)
$\mathcal{M}_*$	$S_? \mathcal{U} S_!$	p (referential reachability probability) and κ_i (condition numbers)

where Δ is a sufficiently small positive number. Equation (1) implies that (i) the “idealized” value of (z_1, z_2, z_3, z_4) , which we call a *reference* to the distribution parameter, is $(\frac{3}{8}, \frac{1}{8}, \frac{1}{4}, \frac{1}{4})$ and (ii) a small perturbation of (z_1, z_2, z_3, z_4) is allowed and measured. A typical model checking problem for this example can be stated as “what is the probability that the frog eventually reaches the fourth rock without landing on the third rock?” Again, well-established model checking techniques do not directly allow one to obtain a solution to this question.

Approach. In a nutshell, the aforementioned two examples demonstrate that a satisfactory model checking result for a probabilistic system with one or more perturbed distribution parameters should shed light on the *sensitivity* of the result to the distribution parameters. In this paper, we provide a method to compute the (*local*) *asymptotic bounds* of the results in terms of *condition numbers* for reachability checking of probabilistic systems under perturbations. We model the probabilistic systems in discrete-time Markov chains (MCs)¹ with distribution parameters, which are coined as *parametric Markov chains* (PMCs), and introduce the *norm of absolute distance* to measure the deviation distances of their distribution parameters (as exemplified by equation (1)). The reachability checking is formalized as follows: given a PMC $\mathcal{M}_*$ with state space S and two sets of states $S_?, S_! \subseteq S$, a reachability problem is phrased as the probability of “reaching states in $S_!$ only via states in $S_?$ ”. By adopting notations from temporal logic, the problem is denoted by $S_? \mathcal{U} S_!$, where $\mathcal{U}$ refers to the “until” operator.² Two instances of the reachability problem class are mentioned in the two motivating examples above. The output of the reachability checking consists of a referential probabilistic result $p \in [0, 1]$ and a condition number $\kappa_i \in \mathbb{R}$ where $i \in I$, an index set, for *each* distribution parameter. The significance of the output is that, if a sufficiently small perturbation Δ_i , measured by the norm of absolute distance, occurs on the parameter whose condition number is κ_i for each $i \in I$, then the actual result is asymptotically bounded by $p \pm \sum_{i \in I} \kappa_i \Delta_i$. A brief comparison of the reachability checking in MCs and PMCs in terms of input and output is presented in Table 1.

¹ Throughout the paper, unless mentioned otherwise, by MCs we mean discrete-time Markov chains.

² In fact, the formulation of reachability in the present paper is slightly more general than the standard definition of reachability and sometimes is called *constrained reachability*, since the $S_?$ in $S_? \mathcal{U} S_!$ plays a constraining role.

Our work is related to a line of research [2,3,4,5], which pursues the perturbation bounds of stationary distributions for MCs. However, to the best of our knowledge, this paper is the first paper devoted to the application of concepts and methods from perturbation theory to the analysis of quantitative verification. To further explain our method, it is beneficial to compare it with a standard method for measurement error estimation based on differentiation and linear approximation. Suppose a sphere (such as a prototype of balls produced by a sporting goods factory) is measured and its radius is $21cm$ with a possible small error within $0.05cm$. The dependence of the sphere volume on the radius is given by $V = \frac{4}{3}\pi r^3$. The problem is to compute volume error V_Δ given the radius error r_Δ . We recall a classic method for this problem: First, the differential function of V on r is given by $dV = 4\pi r^2 dr$. Second, let $dr = r_\Delta = 0.05cm$ (which is significantly small compared with $r = 21cm$) and we obtain $V_\Delta \approx dV = 4\pi \times 21^2 \times 0.05 \approx 277cm^3$. The sensitivity of V_Δ to r_Δ is approximated by the ratio $\frac{dV}{dr} = 4\pi r^2 \approx 5,542$ and this expression is useful if the value of r_Δ is unknown in advance. We aim to develop a similar methodology to estimate the perturbations of reachability in PMCs, which is comparable to the use of differentiation and linear approximation in estimating the error of the ball volume described above.

Organization. The remainder of the paper is organized as follows. In the next section (Section 2), we present the formulations of PMCs and introduce the norm of absolute distance for probabilistic distributions. For presentation purposes, we separate the treatment of PMCs into that of basic PMCs, which have a single distribution parameter, and non-basic PMCs, which have multiple distribution parameters. In Section 3, we deal with basic PMCs by establishing a method for computing their asymptotic bounds, in particular, condition numbers for the given reachability problems. In Section 4, we generalize the computation method to handle non-basic PMCs. We evaluate our approach by experiments in Section 5. Related work is discussed in Section 6. In Section 7, the paper is concluded and several future research directions are outlined.

2 Parametric Markov Chains

In this section, we define the formal models of PMCs, which are parametric variants of MCs. Informally speaking, a PMC is obtained from an MC by replacing the non-zero entries in one or more rows of its probabilistic transition matrix by mutually distinct variables.

Let $\mathbf{x}$ be a symbolic vector of variables, *vector variable* for short, $(x_1, \dots, x_k)$ for some $k \geq 2$ such that $x_{j_1} \neq x_{j_2}$ if $j_1 \neq j_2$. Similar to numerical vectors, we use $\mathbf{x}[j]$ to denote the variable in the i th entry of $\mathbf{x}$. Two vector variables are *disjoint* if they share no common variables. Let $(\mathbf{x}_i)_{i \in I}$ be a sequence of pair-wise disjoint vector variables for some index set $I \neq \emptyset$. Let $\mathbf{x}^*$ be an *extension* of $\mathbf{x}$ obtained by inserting the number zero into $\mathbf{x}$, i.e.,

$$\mathbf{x}^* = (\underbrace{0, \dots, 0}_{l_0 \text{ 0's}}, \mathbf{x}[1], \dots, \mathbf{x}[j], \underbrace{0, \dots, 0}_{l_j \text{ 0's}}, \mathbf{x}[j+1], \dots, \mathbf{x}[k], \underbrace{0, \dots, 0}_{l_k \text{ 0's}}) ,$$

for some $l_0, \dots, l_k \in \mathbb{N}$. Such $\mathbf{x}^*$ is called a *distribution parameter*. We extend each vector variable in $(\mathbf{x}_i)_{i \in I}$ in similar ways to obtain a sequence of distribution parameters such that $|\mathbf{x}_{i_1}^*| = |\mathbf{x}_{i_2}^*| \geq \max(I)$ for each $i_1, i_2 \in I$ (note that $|\mathbf{x}_{i_1}|$ and $|\mathbf{x}_{i_2}|$ are not necessarily the same). Let $\mathbf{c} \in (0, 1)^k$ be a probability distribution, where $k = |\mathbf{x}|$. Thus, $\sum_{j=1}^k \mathbf{c}[j] = 1$. Let $\mathbf{c}^*$ be an ‘extension’ of $\mathbf{c}$ in the same way as $\mathbf{x}^*$ of $\mathbf{x}$, i.e.,

$$\mathbf{c}^* = (\underbrace{0, \dots, 0}_{l_0 \text{ 0's}}, \mathbf{c}[1], \dots, \mathbf{c}[j], \underbrace{0, \dots, 0}_{l_j \text{ 0's}}, \mathbf{c}[j+1], \dots, \mathbf{c}[k], \underbrace{0, \dots, 0}_{l_k \text{ 0's}}) .$$

We call $\mathbf{c}^*$ a *reference* to $\mathbf{x}^*$. Similarly, let each vector in $(\mathbf{c}_i^*)_{i \in I}$ be a reference to the corresponding vector variable in $(\mathbf{x}_i^*)_{i \in I}$. For convenience, we write $(\mathbf{x}_i)_{i \in I}$ (resp., $(\mathbf{x}_i^*)_{i \in I}$) as $\mathbf{x}_I$ (resp., $\mathbf{x}_I^*$), and $(\mathbf{c}_i)_{i \in I}$ (resp., $(\mathbf{c}_i^*)_{i \in I}$) as $\mathbf{c}_I$ (resp., $\mathbf{c}_I^*$). We also call $\mathbf{c}_I^*$ a *reference* to $\mathbf{x}_I$.

Let $\mathcal{P}$ be a *transition matrix* such that $\mathcal{P}[i, j] = \mathbf{c}_i^*[j]$ for each $i \in I$. A *parametric transition matrix* $\mathcal{P}(\mathbf{x}_I^*)$ of $\mathcal{P}$ is obtained by replacing $\mathbf{c}_i^*$ (the probability distribution in the i th row of $\mathcal{P}$) with $\mathbf{x}_i^*$ for each $i \in I$. We call $\mathcal{P}$ a *reference matrix* to $\mathcal{P}(\mathbf{x}_I^*)$. If the distribution parameters are clear in the context, we may just write $\mathcal{P}_*$ for short.

Definition 1 A parametric Markov chain (PMC) is given by the tuple

$$\mathcal{M}_* = (\iota, \mathcal{P}(\mathbf{x}_I^*), \mathbf{c}_I^*) ,$$

where ι is an initial distribution, $\mathcal{P}(\mathbf{x}_I^*)$ is a parametric transition matrix, and $\mathbf{c}_I^*$ is a reference to $\mathbf{x}_I^*$.

Although $\mathbf{c}_I$ can be derived from $\mathcal{P}$ and $\mathbf{x}_I^*$, for readability we present it explicitly in the formulation of $\mathcal{M}_*$. The underlying MC of $\mathcal{M}_*$ is $\mathcal{M} = (\iota, \mathcal{P})$. We do not specify the state space S for $\mathcal{M}_*$ and $\mathcal{M}$. But throughout the paper, we assume that $S = \{1, \dots, |\iota|\}$.

As promised earlier, we introduce a statistical distance measurement between distribution parameters and their references, which is given by the norm of absolute distance (also called total variation).

Definition 2 The statistical distance for $\mathcal{M}_*$ is given by $\|\cdot\|$ such that $\|\mathbf{a}\| = \sum_{i=1}^n |\mathbf{a}[i]|$ for any vector $\mathbf{a}$.

By definitions, the scalar function $\|\mathbf{x}^* - \mathbf{c}^*\|$ is the same as the scalar function $\|\mathbf{x} - \mathbf{c}\|$. If I is a singleton, we also call the PMC a *basic PMC* and denote it as $\mathcal{M}_*^b$. In other words, a basic PMC $\mathcal{M}_*^b$ is a PMC with a single distribution parameter.

We now present examples of PMCs. The first example of PMCs $\mathcal{M}_*^{\text{fg}}$ is for the hopping frog. Its parametric transition matrix (i.e. a 4×4 symbolic matrix) of which is presented in the Introduction and we denote it as $\mathcal{P}_*^{\text{fg}}$. In $\mathcal{P}_*^{\text{fg}}$, the tuple (z_1, z_2, z_3, z_4) is given as the only distribution parameter. We let the reference to the parameter be $(0.375, 0.125, 0.25, 0.25)$. In words, ideally, the probabilities for the frog to jump from the first rock to the first, second, third, and fourth rocks are 0.375, 0.125, 0.25, and 0.25, respectively. Such a PMC is denoted by $\mathcal{M}_*^{\text{fg}}$. Additionally, we let the initial distribution in $\mathcal{M}_*^{\text{fg}}$ be $\iota^{\text{fg}} = (0.25, 0.25, 0.25, 0.25)$, which means that all rock have an equal probability to be the frog's initial position. Clearly, $\mathcal{M}_*^{\text{fg}}$ is a basic PMC.

Another example of PMCs $\mathcal{M}_*^{\text{zf}}$ is for the noisy Zeroconf. For illustration purposes, a probabilistic transition system with a parameter x is provided in Figure 1. The formulation of $\mathcal{M}_*^{\text{zf}}$ according to Definition 1 deviates from the transition system because of the use of distribution variables. Following the definition, we let the sequence of distribution parameters be $(x_i, x'_i)_{i=1}^4$, where $x_i + x'_i = 1$ for each $1 \leq i \leq 4$. The parametric transition matrix $\mathcal{P}_*^{\text{zf}}$ is given by the following 7×7 symbolic matrix:

$$\begin{pmatrix} 0 & a & 0 & 0 & 0 & 0 & 1-a \\ x_1 & 0 & x'_1 & 0 & 0 & 0 & 0 \\ x_2 & 0 & 0 & x'_2 & 0 & 0 & 0 \\ x_3 & 0 & 0 & 0 & x'_3 & 0 & 0 \\ x_4 & 0 & 0 & 0 & 0 & x'_4 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{pmatrix}$$

where the (i, j) -entry in the matrix gives the transition probability from the i th state to the j th state. Because the intended initial state is the first state, the initial distribution ι^{zf} is $(1, 0, \dots, 0)$. The references are obtained by placing 0.75 and 0.25 in the positions of x_i and x'_i , respectively, for each $1 \leq i \leq 4$. In other words, we suppose that under idealized conditions the chances of not receiving a reply in four probes are equivalently 0.25.

3 Perturbation Analysis of Basic PMCs

From this section, we commence the perturbation analysis of reachability problems in PMCs. For presentation purposes, in this section we deal with basic PMCs. Recall that a basic PMC has a single distribution parameter. Our main goal is to establish a method to compute an asymptotic bound, in particular, a condition number for a given reachability problem in a basic PMC against the perturbation of its sole distribution parameter. In the next section, we generalize the method to the setting of PMCs in general.

3.1 Perturbation Function

The reachability problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*^b$ with state space S such that $S_? \cup S_! \subseteq S$ is formulated in the same way as in $\mathcal{M}$. For convenience, we let $S_? = \{1, \dots, n_?\}$

and $S_l = \{n_l, \dots, |\iota|\}$, where $0 \leq n_l < n_l \leq |\iota|$. Thus, $S_l \cap S_l = \emptyset$.³ We call S_l the *constraint* set of $S_l \setminus S_l$ and S_l its *destination* set.

We use $\mathbf{x}_l^*$ to denote the sub-tuple of $\mathbf{x}^*$, the only distribution parameter in $\mathcal{M}_*^b$, such that $\mathbf{x}_l^*$ consists of the first n_l entries in $\mathbf{x}^*$, and $\widehat{\mathbf{x}}_l^*$ to denote the expression $\mathbf{x}^*[n_l] + \dots + \mathbf{x}^*[|\iota|]$. Similarly, let $\mathbf{c}_l^*$ be the first n_l entries of $\mathbf{c}$ and $\widehat{\mathbf{c}}_l^*$ be the sum $\mathbf{c}^*[n_l] + \dots + \mathbf{c}^*[|\iota|]$. Also, let ι_l be the first n_l entries of ι .

Let $\mathbf{p}$ be a vector such that $|\mathbf{p}| = n_l$ and $\mathbf{p}[i]$ is the satisfaction probability of $S_l \cup S_l$ in state i , for each $i \in S_l$. Informally, let

$$\mathbf{p}[i] = \sum_{j=1}^{n_l} \mathcal{P}[i, j] \cdot \mathbf{p}[j] + \sum_{j'=n_l}^{|\iota|} \mathcal{P}[i, j'] , \quad (2)$$

for each $1 \leq i \leq n_l$. We rewrite the equation system given in (2) as

$$\mathbf{p} = \mathbf{A} \cdot \mathbf{p} + \mathbf{b} , \quad (3)$$

where $\mathbf{A}$ is an $n_l \times n_l$ matrix such that $\mathbf{A}[i, j] = \mathcal{P}[i, j]$, and $\mathbf{b}$ is an n_l -vector such that $\mathbf{b}[i] = \sum_{j'=n_l}^{|\iota|} \mathcal{P}[i, j']$. We define $\mathbf{p}$ as the least fixed point satisfying equation (3).

Lemma 3 $\mathbf{p}$ is computed by

$$\mathbf{p} = \sum_{i=0}^{\infty} \mathbf{A}^i \cdot \mathbf{b} . \quad (4)$$

In the following, we define parametric variants of $\mathbf{A}$ and $\mathbf{b}$ specified in equations (3) and (4): Let $\mathbf{A}_{\mathbf{x}_l^*}$ be the parametric matrix obtained by replacing the *first* row in $\mathbf{A}$ with the tuple $\mathbf{x}_l^*$, and $\mathbf{b}_{\widehat{\mathbf{x}}_l^*}$ be the parametric vector by replacing the element in the *first* entry of $\mathbf{b}$ with the polynomial $\widehat{\mathbf{x}}_l^*$. ($\mathbf{A}_{\mathbf{x}_l^*}$ can be seen as the up-left $n_l \times n_l$ sub-matrix of $\mathcal{P}(\mathbf{x}^*)$.) The selection of the first row (resp. entry) in $\mathbf{A}$ (resp. $\mathbf{b}$) should not harm the generality, because we can freely change the row positions in $\mathcal{P}$ in advance. If $\mathbf{x}^*$, n_l and n_l are clear in the context, we also write $\mathbf{A}_{\mathbf{x}_l^*}$ and $\mathbf{b}_{\widehat{\mathbf{x}}_l^*}$ as $\mathbf{A}_*$ and $\mathbf{b}_*$, respectively.

As an example, consider the following model checking problem of the hopping frog (which has already been mentioned in Sections 1 and 2): What is the probability of reaching the fourth rock without landing on the third one? In this problem, the constraint set is $\{1, 2\}$ and the destination set is $\{4\}$. Recall that the only distribution parameter in $\mathcal{M}_*^{\text{fg}}$ is (z_1, z_2, z_3, z_4) . Thus, the parametric matrix and the parametric vector are respectively given by

$$\mathbf{A}_*^{\text{fg}} = \begin{pmatrix} z_1 & z_2 \\ \frac{3}{8} & \frac{1}{8} \end{pmatrix} , \quad \mathbf{b}_*^{\text{fg}} = \begin{pmatrix} z_4 \\ \frac{1}{4} \end{pmatrix} .$$

Let $\mathbf{V} = [0, 1]^k$ where $k = |\mathbf{x}|$ and $\mathbf{U} = \{\mathbf{a} \in \mathbf{V} \mid \sum_{i=1}^n \mathbf{a}[i] = 1\}$.

³ It should be noted that this assumption does not impose any theoretical restriction on the reachability problem. If $S_l \cap S_l \neq \emptyset$, we can carry out the analysis based on $(S_l \setminus S_l) \cup S_l$.

Definition 4 The perturbation function of $\mathbf{x}$ (for the problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*^b$ with reference $\mathbf{c}$) is defined by $\rho : \mathbf{V} \rightarrow [-1, 1]$ such that

$$\begin{aligned} \rho(\mathbf{x}) &= \sum_{i=1}^{n_?} \iota[i] \sum_{j=0}^{\infty} \left(\mathbf{A}_{\mathbf{x}_?^*}^j \cdot \mathbf{b}_{\widehat{\mathbf{x}}_!^*} - \mathbf{A}^j \cdot \mathbf{b} \right) [i] \\ &= \iota_? \cdot \sum_{j=0}^{\infty} \left(\mathbf{A}_{\mathbf{x}_?^*}^j \cdot \mathbf{b}_{\widehat{\mathbf{x}}_!^*} - \mathbf{A}^j \cdot \mathbf{b} \right) . \end{aligned} \quad (5)$$

The perturbation function ρ captures the effect of any small variation of $\mathbf{x}$ with respect to $\mathbf{c}$ on the satisfaction probability of the problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*^b$. For convenience, we call $\mathbf{c}$ the reference of ρ .

3.2 Asymptotic Bounds

There are various ways to express the asymptotic bounds. We adopt the most basic way: The bounds are given by the so-called *absolute condition numbers*. In Section 6 we briefly discuss the terminologies of perturbation bounds and condition numbers.

Let $\Delta > 0$ represent the perturbation distance of a distribution parameter. In reality, we usually assume Δ as a sufficiently small positive number. The following auxiliary definition captures the variation range of ρ with respect to the perturbation distance Δ of the distribution parameter $\mathbf{x}^*$.

Definition 5 The variation range of ρ (with reference $\mathbf{c}$) by Δ is the set

$$\overline{\rho}(\Delta) = \{\rho(\mathbf{a}) \mid \|\mathbf{a} - \mathbf{c}\| \leq \Delta, \mathbf{a} \in \mathbf{U}\} . \quad (6)$$

It is not hard to see that $\overline{\rho}(\Delta)$ is an interval. The existence of a condition number for ρ depends on the differentiability of ρ . The following proposition confirms that ρ enjoys this property in a “neighborhood” of $\mathbf{c}$. Recall that we have assumed $|\mathbf{x}| = k$.

Proposition 6 ρ is differentiable at $\mathbf{c}$, i.e.

$$\rho(\mathbf{y} + \mathbf{c}) = \mathbf{h} \cdot \mathbf{y} + \theta(\mathbf{y}) , \quad (7)$$

for some $\mathbf{h} \in \mathbb{R}^k$ and $\theta : \mathbb{R}^k \rightarrow \mathbb{R}$ such that $\lim_{\|\mathbf{y}\| \rightarrow 0} \theta(\mathbf{y}) / \|\mathbf{y}\| = 0$.

In other words, $\mathbf{h} \cdot \mathbf{y}$ is used as the *linear approximation* of ρ at a point sufficiently close to $\mathbf{c}$, and we write $\rho(\mathbf{y} + \mathbf{c}) \approx \mathbf{h} \cdot \mathbf{y}$. Let $\max(\mathbf{h}) = \max\{\mathbf{h}[i] \mid 1 \leq i \leq |\mathbf{h}|\}$ and $\min(\mathbf{h}) = \min\{\mathbf{h}[i] \mid 1 \leq i \leq |\mathbf{h}|\}$.

Theorem 7 The asymptotic bound of ρ is given by the condition number

$$\kappa = \lim_{\Delta \rightarrow 0} \sup \left\{ \frac{x}{\delta} \mid x \in \overline{\rho}(\delta), 0 < \delta \leq \Delta \right\} . \quad (8)$$

Then, the number κ exists and, moreover,

$$\kappa = \frac{1}{2}(\max(\mathbf{h}) - \min(\mathbf{h})) , \quad (9)$$

where $\mathbf{h}$ is given in Equation (7).

According to the definition of κ in Theorem 7 (in particular, equation (8)), mathematically, if the parameter $\mathbf{x}$ in a basic PMC $\mathcal{M}_*^b$ with reference $\mathbf{c}$ varies an infinitesimally small Δ from $\mathbf{c}$ in terms of the absolute distance, then the perturbation of the reachability checking result, $\rho(\Delta)$, is estimated to be within $\pm\kappa\Delta$, where κ is the condition number of ρ . We test the applicability of such κ in experiments in Section 5.

The definition of κ captures the sensitivity of ρ to $\mathbf{x}$: How does ρ change if we perturb $\mathbf{x}$? A closely related problem is phrased as this: How much do we have to perturb $\mathbf{x}$ to obtain an approximation of ϱ —in other words, what is the backward error of ρ ? The following proposition gives a “backward” characterization of the asymptotic bound κ , which, by its formulation, pursues the infimum of variations of $\mathbf{x}$ (or equivalently, the supremum of their reciprocals) that can cause the given perturbation of ρ .

Proposition 8 *Let κ be defined as in Theorem 7.*

$$\kappa = \lim_{x \rightarrow 0} \sup \left\{ \frac{y}{\delta} \mid 0 < y \leq x, y \in \overline{\rho}(\delta) \right\} . \quad (10)$$

In the following, we present a method to compute the linear approximation of ρ . We write $\sum_{i=0}^{\infty} \mathbf{A}^i$ as $\sum \mathbf{A}$. We define two specific parametric components: $\mathbf{D}_{\mathbf{y}_?^*}$ is the $n_? \times n_?$ parametric matrix such that $\mathbf{D}_{\mathbf{y}_?^*}[1, j] = \mathbf{y}_?^*[j]$ and all other entries in it are zero; and $\mathbf{d}_{\widehat{\mathbf{y}}_!^*}$ is the $n_?$ parametric vector such that $\mathbf{d}_{\widehat{\mathbf{y}}_!^*}[1] = \widehat{\mathbf{y}}_!^*$ and all other entries in it are zero.

Theorem 9 *Let*

$$\mathbf{Q} = \sum \mathbf{A} \cdot \mathbf{D}_{\mathbf{y}_?^*} \cdot \sum \mathbf{A} \cdot \mathbf{b} + \sum \mathbf{A} \cdot \mathbf{d}_{\widehat{\mathbf{y}}_!^*} . \quad (11)$$

Then, $\rho(\mathbf{y} + \mathbf{c}) \approx \iota_? \cdot \mathbf{Q}$.

Theorems 7 and 9 together provide algorithmic techniques for computing the condition number κ for $\mathcal{M}_*^b$ and the reachability problem $S_? \mathcal{U} S_!$.

4 Perturbation Analysis of General PMCs

In this section, we generalize the method developed in the previous section from basic PMCs to general PMCs that may have multiple distribution parameters. For general PMCs, perturbations of the parameters may vary either proportionally or independently, yielding two forms of asymptotic bounds or, equivalently, condition numbers. However, it turns out that the two forms of bounds coincide.

4.1 Directional Conditioning

For general PMCs, we need to handle multiple distribution parameters. The reachability problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*$ is the same as in $\mathcal{M}_*^b$. In this subsection, we suppose their perturbations are subject to a prescribed ratio, i.e., proportionally.

Hence, we associate a function $w : I \rightarrow [0, 1]$ of to $\mathbf{x}_I$ such that $\sum_{i \in I} w(i) = 1$. Such w is called a *direction* of $\mathbf{x}_I$.

To enable the formal treatment, we first give some notation definitions. For each $i \in I$, let $\mathbf{V}_i = [0, 1]^{k_i}$ where $k_i = |\mathbf{x}_i|$. Let $\mathbf{U}_i = \{\mathbf{a} \in \mathbf{V}_i \mid \sum_{j=1}^{k_i} \mathbf{a}[j] = 1\}$. If $I = \{i_1, \dots, i_m\}$, then $\mathbf{V}_I$ denotes the cartesian space $\mathbf{V}_{i_1} \times \dots \times \mathbf{V}_{i_m}$ and $\mathbf{U}_I$ has the similar meaning. Let $n_?, n_!$ have the same meaning as in the previous section. We use $\mathbf{x}_{i,?}^*$ to denote the sub-tuple of $\mathbf{x}_i^*$ which consists of the first $n_?$ variables in $\mathbf{x}_i^*$, and $\widehat{\mathbf{x}}_{i,!}^*$ to denote the expression $\mathbf{x}_i^*[n_!] + \dots + \mathbf{x}_i^*[\iota]$. Let $\mathbf{c}_{i,?}^*$ be the the first $n_?$ entries of $\mathbf{c}_i$ and $\widehat{\mathbf{c}}_{i,!}^*$ be the sum $\mathbf{c}_i^*[n_!] + \dots + \mathbf{c}_i^*[\iota]$. Let $\mathbf{x}_{I,?}^* = (\mathbf{x}_{i,?}^*)_{i \in I}$, $\widehat{\mathbf{x}}_{I,!}^* = (\widehat{\mathbf{x}}_{i,!}^*)_{i \in I}$, $\mathbf{c}_{I,?}^* = (\mathbf{c}_{i,?}^*)_{i \in I}$, and $\widehat{\mathbf{c}}_{I,!}^* = (\widehat{\mathbf{c}}_{i,!}^*)_{i \in I}$. Let $\mathbf{A}_{\mathbf{x}_{I,?}^*}$ be the parametric matrix obtained by replacing the i th row with the tuple $\mathbf{x}_{i,?}^*$ for each $i \in I$, and $\mathbf{b}_{\widehat{\mathbf{x}}_{I,!}^*}$ be the parametric vector obtained by replacing the i th entry with the expression $\widehat{\mathbf{x}}_{i,!}^*$ for each $i \in I$. As before, if $\mathbf{x}^*$ is clear in the context, we write $\mathbf{A}_*$ and $\mathbf{b}_*$ for $\mathbf{A}_{\mathbf{x}_{I,?}^*}$ and $\mathbf{b}_{\widehat{\mathbf{x}}_{I,!}^*}$, respectively.

We illustrate these definitions by the example of noisy Zeroconf, whose model is a non-basic PMC. Clearly, the pursuit of the problem “what is probability of an IP collision?” is equivalent to the problem “what is probability to avoid an IP collision?” In the second problem, the constraint set is $\{1, \dots, 5\}$ and the destination set is $\{7\}$. The sequence of parameters is $(x_i, 1 - x_i)_{i=1}^4$. Thus,

$$\mathbf{A}_*^{\text{zf}} = \begin{pmatrix} 0 & a & 0 & 0 & 0 \\ 1 - x_1 & 0 & x_1 & 0 & 0 \\ 1 - x_2 & 0 & 0 & x_2 & 0 \\ 1 - x_3 & 0 & 0 & 0 & x_3 \\ 1 - x_4 & 0 & 0 & 0 & 0 \end{pmatrix}, \quad \mathbf{b}_*^{\text{zf}} = \begin{pmatrix} 1 - a \\ 0 \\ 0 \\ 0 \\ 0 \end{pmatrix}$$

The following definition generalizes Definition 4.

Definition 10 *The perturbation function of $\mathbf{x}_I$ (for the problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*$ with reference $\mathbf{c}_I$) is defined by $\varrho : \mathbf{V}_I \rightarrow [-1, 1]$ such that*

$$\begin{aligned} \varrho(\mathbf{x}_I) &= \sum_{i=1}^{n_?} \iota[i] \sum_{j=0}^{\infty} (\mathbf{A}_{\mathbf{x}_{I,?}^*}^j \cdot \mathbf{b}_{\widehat{\mathbf{x}}_{I,!}^*} - \mathbf{A}^j \cdot \mathbf{b})[i] \\ &= \iota_? \cdot \sum_{j=0}^{\infty} (\mathbf{A}_{\mathbf{x}_{I,?}^*}^j \cdot \mathbf{b}_{\widehat{\mathbf{x}}_{I,!}^*} - \mathbf{A}^j \cdot \mathbf{b}) \end{aligned} \quad (12)$$

The perturbation function ϱ captures the effect of the small variation of $\mathbf{x}_i$ with respect to $\mathbf{c}_i$ for each $i \in I$ on the reachability problem $S_? \mathcal{U} S_!$ in $\mathcal{M}_*$. We also call $\mathbf{c}_I$ the reference of ϱ . The following definition generalizes Definition 5.

Definition 11 *The w -direction variation range of ϱ (with stationary vector $\mathbf{c}$) against Δ is the set*

$$\overline{\varrho}_w(\Delta) = \{\varrho(\mathbf{a}_I) \mid \|\mathbf{a}_i - \mathbf{c}_i\| \leq w(i)\Delta, \mathbf{a}_i \in \mathbf{U}_i, i \in I\}, \quad (13)$$

where $\mathbf{a}_I = (\mathbf{a}_i)_{i \in I}$.

It is not hard to see that $\bar{\varrho}_w(\Delta)$ is an interval. Suppose $|\mathbf{y}_i| = |\mathbf{c}_i|$ for each $i \in I$ and $\mathbf{y}_I + \mathbf{c}_I$ is the sequence $(\mathbf{y}_i + \mathbf{c}_i)_{i \in I}$. Let $\|\mathbf{y}_I\|$ be $\sum_{i \in I} \|\mathbf{y}_i\|$. Similar to ρ , the following proposition holds for ϱ .

Proposition 12 ϱ is differentiable at $\mathbf{c}_I$, i.e.

$$\varrho(\mathbf{y}_I + \mathbf{c}_I) = \sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i + \theta'(\mathbf{y}_I) \quad (14)$$

where $\mathbf{h}_i \in \mathbb{R}^k$ ($i \in I$) and $\theta' : \mathbb{R}^{k|I|} \rightarrow \mathbb{R}$ such that $\lim_{\|\mathbf{y}_I\| \rightarrow 0} \theta'(\mathbf{y}_I)/\|\mathbf{y}_I\| = 0$.

We write $\varrho(\mathbf{y}_I + \mathbf{c}_I) \approx \sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i$ and call $\sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i$ the *linear approximation* of ϱ at $\mathbf{c}_I$. The following theorem generalizes Theorem 7.

Theorem 13 The w -direction asymptotic bound of ϱ is given by the directional condition number

$$\kappa_w = \lim_{\Delta \rightarrow 0} \sup \left\{ \frac{x}{\delta} \mid x \in \bar{\varrho}_w(\delta), 0 < \delta \leq \Delta \right\} . \quad (15)$$

Then, κ_w exists and, moreover,

$$\kappa_w = \frac{1}{2} \sum_{i \in I} w(i) (\max(\mathbf{h}_i) - \min(\mathbf{h}_i)) , \quad (16)$$

where each $\mathbf{h}_i$ is given in (14).

If the distribution parameters vary a small Δ in the direction w , then we can estimate the perturbation of ρ as $\pm k_w \Delta$. In the case that $w(i) = 1/|I|$ for each $i \in I$, such k_w is called a *uniform* condition number. Like the asymptotic bounds for basic PMCs, a “backward” characterization of κ_w also exists.

Proposition 14 Let κ_w be defined as in Theorem 13.

$$\kappa_w = \lim_{x \rightarrow 0} \sup \left\{ \frac{y}{\delta} \mid 0 < y \leq x, y \in \bar{\varrho}_w(\delta) \right\} . \quad (17)$$

We also provide a method to compute the linear approximation of ϱ . We define two specific parametric matrices. $\mathbf{D}_{\mathbf{y}_{I,?}}^*$ is the $n_I \times n_I$ matrix such that $\mathbf{D}_{\mathbf{y}_{I,?}}^*[i, j] = \mathbf{A}_{\mathbf{y}_{I,?}}^*[i, j]$ for each $i \in I$ and $1 \leq j \leq k$ and all other entries in $\mathbf{D}_{\mathbf{y}_{I,?}}^*$ are zero. $\mathbf{d}_{\hat{\mathbf{y}}_{I,!}}^*$ is the n_I -vector such that $\mathbf{d}_{\hat{\mathbf{y}}_{I,!}}^*[i] = \mathbf{b}_{\hat{\mathbf{y}}_{I,!}}^*[i]$ for each $i \in I$ and all other entries in $\mathbf{d}_{\hat{\mathbf{y}}_{I,!}}^*$ are zero. We have the following generalized theorem of Theorem 9.

Theorem 15 For each $i \in I$, let

$$\mathbf{Q}_I = \sum \mathbf{A} \cdot \mathbf{D}_{\mathbf{y}_{I,?}}^* \cdot \sum \mathbf{A} \cdot \mathbf{b} + \sum \mathbf{A} \cdot \mathbf{d}_{\hat{\mathbf{y}}_{I,!}}^* . \quad (18)$$

Then, $\varrho(\mathbf{y}_I + \mathbf{c}_I) \approx \iota_I \cdot \mathbf{Q}_I$.

Theorems 13 and 15 together provide an algorithmic method for computing the directional condition number κ_w for $\mathcal{M}_*$ and the reachability problem $S_I \mathcal{U} S_I$.

4.2 Parameter-wise Conditioning

The parameter-wise perturbation analysis handles the independent variations of distribution parameters. In this case, to facilitate the perturbation estimation, we expect to obtain a condition number for each distribution parameter. It turns out that the parameter-wise analysis can be reduced to the directional analysis.

We use $\mathbf{c}_I[i := \mathbf{a}]$ denote the sequence of vectors obtained by replacing the i th vector in $\mathbf{c}_I$ by $\mathbf{a}$.

Definition 16 *The variation range of ϱ projected at $\mathbf{x}_i$ against Δ is the set*

$$\overline{\varrho}_i(\Delta) = \{\varrho(\mathbf{c}_I[i := \mathbf{a}]) \mid \|\mathbf{a} - \mathbf{c}_i\| \leq \Delta, \mathbf{a} \in \mathbf{U}_i\} . \quad (19)$$

The asymptotic bound of ϱ projected at $\mathbf{x}_i$ is given by the condition number

$$\kappa_i = \lim_{\Delta \rightarrow 0} \sup \left\{ \frac{x}{\delta} \mid x \in \overline{\varrho}_i(\delta), 0 < \delta \leq \Delta \right\} . \quad (20)$$

Let w_i be the direction such that $w_i(i) = i$ and $w_i(j) = 0$ for each $j \in I \setminus \{i\}$. It is easy to see that $\overline{\varrho}_i$ (resp. κ_i) is just $\overline{\varrho}_{w_i}$ (resp. κ_{w_i}). It means that parameter-wise bounds are special cases of directional bounds. Moreover, the following theorem states that any set of parameter-wise condition numbers conforms to a specific directional condition number.

Theorem 17 *Let $\Delta = \sum_{i \in I} \Delta_i$ and $w(i) = \Delta_i / \Delta$ for each $i \in I$. Then,*

$$\sum_{i \in I} \kappa_i \Delta_i = \kappa_w \Delta . \quad (21)$$

If the direction of perturbation may not be known in advance, it is more useful to present the set of parameter-wise bounds. Theorem 17 provides a mathematical characterization for parameter-wise perturbations in terms of direction perturbations.

5 Experiments

We evaluate by experiments, informally speaking, how well the condition numbers handle possible perturbations of the reachability problem for the PMC under consideration. Recall that the outcome of the reachability checking algorithm for a PMC consists of two parts, namely, a referential probabilistic result and one or more condition numbers (see Table 1). The probabilistic result is computed by a conventional numerical model checking algorithm. In particular, the probability result is given by the equation

$$p = \iota_? \cdot \mathbf{p} + \iota[n_1] + \dots + \iota[[\iota]] , \quad (22)$$

where $\mathbf{p}$ is given in equation (4). For problems considered in this section, only a single condition number will be returned. The condition number is calculated by the method presented in the previous sections.

Table 2. Experimental data of noisy Zeroconf ($\times 10^{-3}$)

Model	x_i	Probability	Distance	Condition Number	Variation Range
$\mathcal{M}_*^{\text{zf}}$	750	999.024	-	7.797	-
$\mathcal{M}_1^{\text{zf}}$	749	-.016	2	-	$\pm .016$
$\mathcal{M}_2^{\text{zf}}$	752	+.031	4	-	$\pm .031$
$\mathcal{M}_3^{\text{zf}}$	747	-.048	6	-	$\pm .047$

Table 3. Experimental data of hopping frog ($\times 10^{-3}$)

Model	Distribution	Probability	Distance	Condition Number	Variation Range
$\mathcal{M}_*^{\text{fg}}$	(375, 125, 250, 250)	500.000	-	312.500	-
$\mathcal{M}_1^{\text{fg}}$	(374, 124, 251, 251)	0	4	-	± 1.250
$\mathcal{M}_2^{\text{fg}}$	(374, 124, 250, 252)	+.623	4	-	± 1.250
$\mathcal{M}_3^{\text{fg}}$	(377, 125, 248, 250)	+.627	4	-	± 1.250
$\mathcal{M}_4^{\text{fg}}$	(377, 125, 250, 248)	-.627	4	-	± 1.250
$\mathcal{M}_4^{\text{fg}}$	(375, 125, 248, 252)	+1.250	4	-	± 1.250
$\mathcal{M}_5^{\text{fg}}$	(375, 125, 252, 248)	-1.250	4	-	± 1.250

Our experiments proceed as follows. (i) We specify a reachability problem for the PMC $\mathcal{M}_*$ and compute the referential probabilistic result p and *one* condition number κ for the problem, although multiple condition numbers may be required in other contexts. (ii) By deliberately assigning concrete probability distributions to the distribution parameter(s) of $\mathcal{M}_*$, we construct several potential non-parametric models $\mathcal{M}_j$ with sufficiently small statistical distances to $\mathcal{M}_*$. (iii) We compute an actual probabilistic result p_j for each $\mathcal{M}_j$ and calculate the actual distance Δ_j between the reference(s) in $\mathcal{M}_*$ and the corresponding distribution(s) in $\mathcal{M}_j$. (iv) We compare $p - p_j$, the difference between the referential result and an actual result, and $\pm \kappa \Delta_j$, the perturbation estimation.

We perform experiments for the examples of noisy Zeroconf and hopping frog, i.e., the PMCs $\mathcal{M}_*^{\text{zf}}$ and $\mathcal{M}_*^{\text{fg}}$, in Matlab[®] [7]. In the hopping frog example, for the ease of calculations, we let a in $\mathcal{P}_*^{\text{zf}}$, the parametric transition matrix of $\mathcal{M}_*^{\text{zf}}$, be 0.2. It is reasonable assume each probe message and its reply are effected by the same channel noise level, namely, that the four distribution parameters of $\mathcal{M}_*^{\text{zf}}$ are perturbed in a uniform direction. Several MCs in both experiments are generated by assigning different distributions to the distribution parameters in their PMCs. Because the infinite matrix series $\sum_{i=0}^{\infty} \mathbf{A}^i$ cannot be computed directly, we adopt an approximation by taking the sum of the first hundred items in each series encountered. There is no significant truncation error involved the numerical calculation in our experiments. We test the reachability problems $\{1, \dots, 5\} \mathcal{U} \{7\}$ in the first experiment (which states “what is the probability to avoid an IP collision?”) and $\{1, 2\} \mathcal{U} \{4\}$ in the second one (which states “what is the probability for the frog to reach the fourth rock without landing on the third

rock?"). The experimental data are summarized in Figures 2 and 3, respectively. In Figure 2, the distance of the perturbed models to the PMC increases. We observe that the condition number accounts for the result nicely if the perturbed distance is smaller than 0.006. When the distance exceeds 0.006, the perturbation of the probabilistic result may drop out of the variation range. In Figure 3, several perturbed models with the distance 0.004 to the PMC are inspected. The data also demonstrate that the condition number bounds the reachability perturbation between a perturbed model and the PMC to a satisfactory degree. In particular, the difference between the result for $\mathcal{M}_4^{\text{fg}}$ (resp., $\mathcal{M}_5^{\text{fg}}$) and the referential result overlaps with the positive (resp., negative) predicted bound.

In short, we observe from the experiments that condition numbers adequately, although not rigorously, predict the bounds of the reachability checking results if distribution parameters perturbations are sufficiently small.

6 Related Work

Our work is related to the study of perturbations of MCs, which pursues perturbation bounds for their stationary distributions, and which can be traced back to 1960's. Indeed, from the technical point of view, reachability and the stationary distribution have an intrinsic connection, and so do their perturbations. Schweitzer [2] gave the first perturbation bound, namely, an absolute condition number for the stationary distribution of an MC against its fundamental matrix (which is defined by the transition matrix of the MC), and motivated a variety of subsequent work. Cho and Meyer [3] provided an excellent overview on various bounds of stationary distributions (all of which are in the forms of condition numbers) up to the written time, whilst more recent papers in this line of research include [4] and [5], both of which shed light on new definitions and techniques for perturbation bounds. In spite of its relatively long history, to the best of our knowledge, the present paper is the first paper that raises the perturbation problem in quantitative verification.

In a more general setting, the main goal of perturbation theory for numerical linear algebra [8] is to investigate the sensitivity of given problems with respect to the perturbed input data in a prescribed domain and provide various forms of perturbation bounds for the problems. One important group of such bounds is called asymptotic bounds (also called linear local bounds), which is further divided into two subgroups, i.e., absolute condition numbers and relative condition numbers. The condition numbers for the reachability verification pursued in the present paper belong to the first subgroup. Both subgroups of condition numbers have their significance: absolute condition numbers enjoy a more elegant mathematical formulation and are easier to be employed to analyze practical problems, whilst relative ones are more important to floating point arithmetic implemented in every computer, which is affected by relative rather than absolute errors. A detailed classification of these bounds is found in [9] (Chapters 1 and 2). We leave the analysis of our problem based on other kinds of bounds to future work.

There have been many efforts that attempted to introduce perturbation errors to realtime systems, in particular, timed automata. For example, Alur *et al* [10] defined a perturbed semantics for timed automata whose clocks might change at some very small rates. They showed that if the automaton has a single clock then the language accepted by it under the perturbed semantics is accepted by a deterministic automaton under the standard semantics. Bouyer *et al* [11] provided another perturbed semantics, which captures not the perturbations of the clock rates but those of the clock constraints. They developed model checking techniques of Büchi and LTL properties based on a novel semantic satisfaction relation, which is defined via their perturbed semantics and captures—as they argued—the intuitive notion “whether the considered property holds for the same model implemented in a sufficient (but not infinitely) fast hardware”. Still another different problem, which studies realtime systems with general dynamic nature, was addressed by Chen *et al* [12], who proposed an LTL model checking method for a continuous-time inhomogeneous (or non-stationary) MC, the inhomogeneity of which is predefined by an integrable function.

Sensitivity of computable problems to their input data are also explored in other contexts. Misailovic *et al* [13] introduced a framework of approximate correctness for programs, one utility of which is to analyze the robustness of programs with disturbed input, namely, whether small perturbations to the input lead to small variations of the output only. Heimdahl *et al* [14] employed model checking techniques in software deviation analysis of control systems.

7 Conclusions

Motivated by the pervasive phenomena of perturbations in the modeling and verification of real-life probabilistic systems, we study the sensitivity of constrained reachability probabilities of those systems, which are modeled by parametric variants of discrete-time MCs, to perturbations of their distribution parameters. Our contribution is a method to compute the asymptotic bounds in terms of absolute condition numbers to characterize the sensitivity. We also conduct experiments to demonstrate the practical adequacy of the computation method.

This paper is an initial step of investigating the sensitivity and bounds for quantitative verifications of systems under perturbations, and several interesting directions for further research are outlined below. First, reachability, in spite of its fundamental status in model checking, captures a narrow group of practical verification problems (particularly in the probabilistic domain) and, therefore, it is desirable to extend the present method to accommodate the general model checking problems formalized, for instance, in the LTL formulas. Second, we adopt the norm of absolute distance to measure the distance between two probability distributions, however, there exist other measurements that are particularly useful for problems in some specific domains. For example, the well-known Kullback-Leibler divergence is widely adopted in information theory [15]. Finally, condition numbers are among several other forms of perturbation bounds. An in-depth comparison of their pros and cons is left to future work.

Acknowledgement

The work of Guoxin Su was carried out when he was a PhD student with the Centre for Quantum Computation and Intelligent Systems (QCIS) at the University of Technology, Sydney. The work of David Rosenblum was supported by grant R-252-000-458-133 from the National University of Singapore. We would like to thank Professor Mingsheng Ying for first pointing us to perturbation theory.

References

1. Kwiatkowska, M., Norman, G., Parker, D.: PRISM 4.0: Verification of probabilistic real-time systems. In Gopalakrishnan, G., Qadeer, S., eds.: Proc. 23rd International Conference on Computer Aided Verification (CAV'11). Volume 6806 of LNCS., Springer (2011) 585–591
2. Schweitzer, P.J.: Perturbation theory and finite markov chains. *Journal of Applied Probability* **5**(2) (1968) 401–413
3. Cho, G.E., Meyer, C.D.: Comparison of perturbation bounds for the stationary distribution of a markov chain. *Linear Algebra Appl* **335** (2000) 137–150
4. Solan, E., Vieille, N.: Perturbed markov chains. *J. Applied Prob* (2003) 107–122
5. Heidergott, B.: Perturbation analysis of markov chains. In: *Discrete Event Systems, 2008. WODES 2008. 9th International Workshop on.* (may 2008) 99–104
- 6.
7. MATLAB: version 8.0 (R2012b). The MathWorks Inc., Natick, Massachusetts (2012)
8. Kato, T.: *Perturbation Theory for Linear Operators* (2ed). Springer-Verlag, Berlin, Heidelberg, New York (2005)
9. Konstantinov, M., Gu, D., Mehrmann, V., Petkov, P.: *Perturbation Theory for Matrix Equations*. ELSEVIER, Amsterdam, The Netherlands (2003)
10. Alur, R., La Torre, S., Madhusudan, P.: Perturbed timed automata. In: *Proceedings of the 8th international conference on Hybrid Systems: computation and control. HSCC'05*, Springer-Verlag (2005) 70–85
11. Bouyer, P., Markey, N., Reynier, P.A.: Robust model-checking of linear-time properties in timed automata. In: *Proceedings of the 7th Latin American conference on Theoretical Informatics. LATIN'06*, Springer-Verlag (2006) 238–249
12. Chen, T., Han, T., Katoen, J.P., Mereacre, A.: LTL model checking of time-inhomogeneous markov chains. In: *Proceedings of the 7th International Symposium on Automated Technology for Verification and Analysis. ATVA'09*, Springer-Verlag (2009) 104–119
13. Misailovic, S., Roy, D.M., Rinard, M.C.: Probabilistically accurate program transformations. In: *Proceedings of the 18th international conference on Static analysis. SAS'11*, Springer-Verlag (2011) 316–333
14. Heimdahl, M.P.E., Choi, Y., Whalen, M.: Deviation analysis through model checking. In: *Proceedings of the 17th IEEE international conference on Automated software engineering. ASE'02*, IEEE Computer Society (2002) 37–46
15. Cover, T.M., Thomas, J.A.: *Elements of information theory*. Wiley-Interscience, New York, NY, USA (1991)
16. Ying, M.: π -calculus with noisy channels. *Acta Informatica* **41** (2005) 525–593
17. Baier, C., Katoen, J.P.: *Principles of Model Checking*. The MIT Press (2008)

Appendix: Proof Details

Proof (Proof of Lemma 3). See Theorem 10.15 and its subsequent remark at pp.762-764 in [17].

Proof (Proof of Proposition 6). We refer this proof to the constructive (and independent) proof of Theorem 9 below.

Proof (Proof of Theorem 7). Let

$$\kappa' = \frac{1}{2}(\max(\mathbf{h}) - \min(\mathbf{h})) = \frac{1}{2}(\mathbf{h}[i_1] - \mathbf{h}[i_2])$$

for some i_1, i_2 , and our goal is to show that κ exists and $\kappa = \kappa'$. Note that $|\mathbf{h}| = k$.

First we give a claim. Let $\mathbf{q} \in [-1, 1]^k$ such that $\hat{\mathbf{q}} = 0$ and $\|\mathbf{q}\| = 1$. We claim that

$$\mathbf{h} \cdot \mathbf{q} \leq \kappa' .$$

The proof of the claim is straightforward.

Let $\varepsilon > 0$. According to Proposition 6, choose $\Delta > 0$ such that if $0 < \|\mathbf{y}\| = \delta \leq \Delta$ then

$$|\mathbf{h} \cdot \mathbf{y} - \rho(\mathbf{y} + \mathbf{c})| \leq \frac{\delta \varepsilon}{2} .$$

Let $\mathbf{y} = \delta \mathbf{q}$, then

$$\left| \mathbf{h} \cdot \mathbf{q} - \frac{\rho(\mathbf{y} + \mathbf{c})}{\|\mathbf{y}\|} \right| = \left| \frac{\mathbf{h} \cdot \mathbf{y} - \rho(\mathbf{y} + \mathbf{c})}{\|\mathbf{y}\|} \right| \leq \frac{\varepsilon}{2} ;$$

in particular,

$$\left| \kappa' - \frac{\rho(r\mathbf{e}_{i_1, i_2} + \mathbf{c})}{\|r\mathbf{e}_{i_1, i_2}\|} \right| \leq \frac{\varepsilon}{2} ,$$

where $\mathbf{e}_{i,j}$ is the vector such that the i th (resp. j th) entry in $\mathbf{e}_{i,j}$ is $1/2$ (resp. $-1/2$) and the other entries (if any) are all zero. Supposing r is sufficiently small, $r\mathbf{e}_{i_1, i_2} + \mathbf{c} \in \mathbf{U}$. Then,

$$\frac{\rho(r\mathbf{e}_{i_1, i_2} + \mathbf{c})}{\delta} \in \left\{ \frac{x}{\delta} \mid x \in \overline{\rho}(\delta), 0 < \delta \leq \Delta \right\} .$$

Thus,

$$\kappa' - \varepsilon \leq \sup \left\{ \frac{x}{\delta} \mid x \in \overline{\rho}(\delta), 0 < \delta \leq \Delta \right\} .$$

On the other hand, given $0 < \delta' < \Delta$, choose $\mathbf{z}_\Delta$ such that $\|\mathbf{z}\| = \delta'$, $\mathbf{z} + \mathbf{c} \in \mathbf{U}$, and $\sup(\bar{\rho}(\delta')) \leq \rho(\mathbf{z} + \mathbf{c}) + \varepsilon\delta'/2$. Without loss of generality, we suppose $\mathbf{z} = \delta'\mathbf{q}'$. Thus,

$$\mathbf{h} \cdot \mathbf{q}' + \varepsilon \geq \frac{\rho(\mathbf{z} + \mathbf{c})}{\delta'} + \frac{\varepsilon}{2}.$$

Thus, $\kappa' + \varepsilon \geq \frac{\sup(\bar{\rho}(\delta))}{\delta}$ for any δ such that $0 < \delta \leq \Delta$. Hence,

$$\kappa' + \varepsilon \geq \sup \left\{ \frac{x}{\delta} \mid x \in \bar{\rho}(\delta), 0 < \delta \leq \Delta \right\}.$$

Therefore, we have proved that κ exists and $\kappa = \kappa'$.

Proof (Proof of Proposition 8). We suffice to show the following two propositions:

1. for each $\varepsilon > 0$ there exists $x > 0$ such that $y/\delta < \kappa + \varepsilon$ whenever $0 < y \leq x$ and $y \in \bar{\rho}(\delta)$;
2. for each $\varepsilon > 0$ and $x > 0$ there exists $0 < y \leq x$ and $\delta > 0$ such that $y \in \bar{\rho}(\delta)$ and $\kappa < y/\delta + \varepsilon$.

On the other hand, by the definition of κ ,

1. for each $\varepsilon > 0$ there exists $\Delta > 0$ such that $y/\delta < \kappa + \varepsilon$ whenever $0 < \delta \leq \Delta$ and $y \in \bar{\rho}(\delta)$;
2. for each $\varepsilon > 0$ and $\Delta > 0$ there exists $0 < \delta \leq \Delta$ and $y > 0$ such that $y \in \bar{\rho}(\delta)$ and $\kappa < y/\delta + \varepsilon$.

It holds that given any $\Delta > 0$ we can choose x such that if $0 < y \leq x$ and $y \in \bar{\rho}(\delta)$ then $0 < \delta \leq \Delta$; conversely, given any $x > 0$ we can choose Δ such that if $0 < \delta \leq \Delta$ and $y \in \bar{\rho}(\delta)$ then $0 < y \leq x$. Therefore, it can be verified that the two sets of propositions are equivalent.

Proof (Proof of Theorem 9). $\rho(\mathbf{x})$ actually defines a system of non-linear (i.e. multi-variable polynomial) series. Given a multi-variable polynomial series, the order of a term in the series is the summation of the exponents of all variants in it. The smallest order of all terms is called least order of the series. By the

definition of $f(\mathbf{x})$, we have that

$$\begin{aligned}
& \rho(\mathbf{y} + \mathbf{c}) \\
&= \iota_{\gamma} \cdot (f(\mathbf{y} + \mathbf{c}) - f(\mathbf{c})) \\
&= \iota_{\gamma} \cdot \left(\sum_{i=0}^{\infty} (\mathbf{A} + \mathbf{D}_{\mathbf{y}_{\gamma}^*})^i \cdot (\mathbf{b} + \mathbf{d}_{\mathbf{y}_{\gamma}^*}) - \sum_{i=0}^{\infty} \mathbf{A} \cdot \mathbf{b} \right) \\
&= \iota_{\gamma} \cdot \left(\sum_{i=0}^{\infty} \mathbf{A}^i \cdot \mathbf{d}_{\mathbf{y}_{\gamma}^*} + \sum_{j=0}^{\infty} \sum_{i=0}^j \mathbf{A}^{i-j} \cdot \mathbf{D}_{\mathbf{y}_{\gamma}^*} \cdot \mathbf{A}^j \cdot \mathbf{b} \right) + \varphi \\
&= \iota_{\gamma} \cdot \left(\underbrace{\sum_{i=0}^{\infty} \mathbf{A}^i \cdot \mathbf{d}_{\mathbf{y}_{\gamma}^*}}_{\psi_1} + \underbrace{\sum_{i=0}^{\infty} \mathbf{A}^i \cdot \mathbf{D}_{\mathbf{y}_{\gamma}^*} \cdot \sum_{i=0}^{\infty} \mathbf{A}^i \cdot \mathbf{b}}_{\psi_2} \right) + \varphi ,
\end{aligned}$$

where φ is either 0 or a of polynomial whose least order is not smaller than 2. Thus,

$$\lim_{\|\mathbf{y}\| \rightarrow 0} \frac{\varphi}{\|\mathbf{y}\|} = 0 .$$

Let $\mathbf{h} \cdot \mathbf{y} = \iota_{\gamma} \cdot (\psi_1 + \psi_2)$, and we obtain equation (7) in Proposition 6, namely

$$\rho(\mathbf{y} + \mathbf{c}) \approx \iota_{\gamma} \cdot (\psi_1 + \psi_2) .$$

Proof (Proof of Proposition 12). We refer this proof to the proof of Theorem 15 below.

Proof (Proof of Theorem 13). The proof is a generalization of the proof of Theorem 7. For any direction w , let

$$\kappa'_w = \frac{1}{2} \sum_{i \in I} w(i) (\max(\mathbf{h}_i) - \min(\mathbf{h}_i)) = \frac{1}{2} \sum_{i \in I} w(i) (\mathbf{h}_i[j_i^1] - \mathbf{h}_i[j_i^2]) ,$$

for some j_i^1, j_i^2 for each $i \in I$. Our goal is to show that κ_w exists and $\kappa_w = \kappa'_w$. Note that $|\mathbf{h}_i| = k$ for each i .

We first give a claim. Let $\mathbf{q}_i \in [-1, 1]^k$ such that, for each $i \in I$, $\sum_{j=1}^k \mathbf{q}_i[j] = 0$ and $\|\mathbf{q}_i\| = 1$. We claim that

$$\sum_{i \in I} w(i) (\mathbf{h}_i \cdot \mathbf{q}_i) \leq \kappa'_w |I| .$$

The claim is not hard to be verified.

Let $\varepsilon > 0$. According to Proposition 12, choose $\Delta > 0$ such that if $0 < \|\mathbf{y}_i\| = \delta w(i) \leq \Delta w(i)$ for any $i \in I$, then

$$\left| \sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i - \varrho(\mathbf{y}_I + \mathbf{c}_I) \right| \leq \frac{\delta \varepsilon}{2} .$$

Let $\mathbf{y}_i = \delta w(i) \mathbf{q}_i$ for each $i \in I$. Thus

$$\left| \sum_{i \in I} w(i) (\mathbf{h}_i \cdot \mathbf{q}_i) - \frac{\varrho(\mathbf{y}_I + \mathbf{c}_I)}{\delta} \right| = \left| \frac{\sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i - \varrho(\mathbf{y}_I + \mathbf{c}_I)}{\delta} \right| \leq \frac{\varepsilon}{2} ;$$

in particular, let $\mathbf{e}_I = (\mathbf{e}_{j_i^1, j_i^2})_{i \in I}$ where $\mathbf{e}_{j_i^1, j_i^2}$ is the vector such that the j_i^1 th (resp. j_i^2 th) entry in it is $1/2$ (resp. $-1/2$) and the other entries (if any) are all zero (thus, $\mathbf{e}_{j_i^1, j_i^2}$ is a particular instance of $\mathbf{q}_i$); then

$$\left| \kappa'_w - \frac{\varrho(\delta w \cdot \mathbf{e}_I + \mathbf{c}_I)}{\delta} \right| \leq \frac{\varepsilon}{2} .$$

Since δ is sufficiently small, $\delta w \cdot \mathbf{e}_I + \mathbf{c}_I \in \mathbf{U}_I$. Then

$$\frac{\varrho(\delta w \cdot \mathbf{e}_I + \mathbf{c}_I)}{\delta} \in \left\{ \frac{x}{\delta} \mid x \in \bar{\varrho}_w(\delta), 0 < \delta \leq \Delta \right\} .$$

Thus,

$$\kappa'_w - \varepsilon \leq \sup \left\{ \frac{x}{\delta} \mid x \in \bar{\varrho}_w(\delta), 0 < \delta \leq \Delta \right\} .$$

On the other hand, given $0 < \delta' \leq \Delta$, choose $\mathbf{z}_I = (\mathbf{z}_i)_{i \in I}$ such that $\|\mathbf{z}_i\| = \delta' w(i)$ for each $i \in I$, $\mathbf{z}_I + \mathbf{c}_I \in \mathbf{U}_I$, and $\sup(\bar{\varrho}(\delta')) \leq \rho(\mathbf{z}_I + \mathbf{c}_I) + \varepsilon \delta'/2$. Without loss of generality, we suppose $\mathbf{z}_i = \delta' \mathbf{q}'_i$ for each $i \in I$. Thus,

$$\sum_{i \in I} \mathbf{h}_i \cdot \mathbf{q}'_i + \varepsilon \geq \frac{\varrho(\mathbf{z}_I + \mathbf{c}_I)}{\delta'} + \frac{\varepsilon}{2} .$$

Thus, $\kappa'_w + \varepsilon \geq \frac{\sup(\bar{\varrho}_w(\delta'))}{\delta'}$. Hence,

$$\kappa'_w + \varepsilon \geq \sup \left\{ \frac{x}{\delta} \mid x \in \bar{\varrho}_w(\delta), 0 < \delta \leq \Delta \right\} .$$

Therefore, we have proved that κ_w exists and $\kappa_w = \kappa'_w$.

Proof (Proof of Proposition 14). The proof is an immediate generalization of the proof of Proposition 8.

Proof (Proof of Theorem 15). The proof of this theorem is a generalization of that of Theorem 9. By the definition of $g(\mathbf{x})$, we have that

$$\begin{aligned} & \varrho(\mathbf{y}_I + \mathbf{c}_I) \\ &= \iota_{\varphi} \cdot (g(\mathbf{y}_I + \mathbf{c}) - g(\mathbf{c}_I)) \\ &= \iota_{\varphi} \cdot \sum_{i \in I} \sum_{j=0}^{\infty} \left(\mathbf{A} + \mathbf{D}_{\mathbf{y}_{I,?}^*} \right)^j \cdot \left(\mathbf{b} + \mathbf{d}_{\mathbf{y}_{I,1}^*} \right) \\ &= \iota_{\varphi} \cdot \left(\underbrace{\sum_{j=0}^{\infty} \mathbf{A}^j \cdot \mathbf{d}_{\mathbf{y}_{I,1}^*}}_{\psi_{I,1}} + \underbrace{\sum_{j=0}^{\infty} \mathbf{A}^j \cdot \mathbf{D}_{\mathbf{y}_{I,?}^*} \cdot \sum_{j=0}^{\infty} \mathbf{A}^j \cdot \mathbf{b}}_{\psi_{I,2}} \right) + \varphi , \end{aligned}$$

where φ is either 0 or a of polynomial whose least order is not smaller than 2. Thus,

$$\lim_{\|\mathbf{y}_I\| \rightarrow 0} \frac{\varphi}{\|\mathbf{y}_I\|} = 0 \ .$$

Let $\sum_{i \in I} \mathbf{h}_i \cdot \mathbf{y}_i = \iota? \cdot (\psi_{i,1} + \psi_{i,2})$, and we obtain equation (14) in Proposition 12, namely

$$\varrho(\mathbf{y}_I + \mathbf{c}_I) \approx \iota? \cdot \sum_{i \in I} (\psi_{i,1} + \psi_{i,2}) \ .$$

Proof (Proof of Theorem 17). It holds that for each $i \in I$

$$\begin{aligned} \kappa_i &= \frac{1}{2}(\max(\mathbf{h}_i) - \min(\mathbf{h}_i)) \\ \kappa_w &= \frac{1}{2} \sum_{i \in I} w(i)(\max(\mathbf{h}_i) - \min(\mathbf{h}_i)) \end{aligned}$$

where $w(i) = \Delta_1/\Delta$ and $\Delta = \sum_{i \in I} \Delta_i$. Equation (21) follows.